



Nexis Click-on Mirro zum Kleben auf Spiegel- oder Glastüren




Voll aufliegend



Halb aufliegend



Einliegend



Montageplattenabstand

X = 37 mm bei Montageplatte mit Lochreihe 28


X = 46 mm bei Montageplatte mit Lochreihe 37

Fugenwert:

Bei Spiegel- oder Glastüren werden Fugen von min. 2mm benötigt, ansonsten besteht Bruchgefahr.

Der Spiegel bzw. das Glas darf nur spannungsfrei montiert werden. Beim Öffnen der Tür ist darauf zu achten, dass keine Berührung mit dem Korpus entsteht.

Position der Scharnieraufnahme



Nexis Click-on Montageplatten Höhe (f)

		Klebmaß (Z) max. 21 mm								
		5	7	9	11	13	15	17	19	21
00	-2	0	2	4	6	8	10	12	14	
02	-4	-2	0	2	4	6	8	10	12	
04	-6	-4	-2	0	2	4	6	8	10	
		Türauflage (e)								

Achtung!




Mirro Scharniere dürfen nicht mit Exzenter Montageplatten verwendet werden.

Verstellbereich:

Höhe: +/- 2mm

Tiefe: +3/-1

Auflage: +/- 2mm



Verarbeitungshinweis:

Bezüglich Auswahl und Verarbeitung des Klebstoffes zur Befestigung der Scharnieraufnahme auf Spiegel- und Glastüren wenden Sie sich bitte an Ihren Glas- bzw. Türlieferant.


Haftungsansprüche:

Wir bitten um Verständnis, dass Grass keine Haftung für den verwendeten Klebstoff und das angewandte Klebverfahren bzw. alle daraus resultierenden Ansprüche übernehmen kann.


Nexis Click-on Mirro hinge, glued fixing, for mirror and glass doors




Full overlay



Half overlay



Inset



Mounting plate fixing distance

X = 37 mm with mounting plate with line boring 28


X = 46 mm with mounting plate with line boring 37

Required gap:

On all type of application a min. 2mm gap is required, otherwise there is a risk of breakage.

The glass or mirror must be installed tension free. While opening the door ensure that the door sides do not interfere with the cabinet.

Hinge adapter fixing position



Nexis Click-on mounting plates height (f)

		Fixing position (Z) max. 21 mm								
		5	7	9	11	13	15	17	19	21
Nexis Click-on mounting plates height (f)	00	-2	0	2	4	6	8	10	12	14
	02	-4	-2	0	2	4	6	8	10	12
	04	-6	-4	-2	0	2	4	6	8	10
		Door overlay (e)								

Attention!




It is not possible to use excenter mounting plates with Mirro hinges.

Adjustments:

Height: +/- 2mm

Depth: +3/-1

Overlay: +/- 2mm



Assembly instructions for stainless steel hinge adapter:

Please call your glass or mirror door supplier for detailed information regarding the adhesive and the gluing process of the stainless steel hinge adapter.

Important information:

Mepla-Alfit cannot be held responsible for the adhesive, adhesive process and adapter plate door connection and any resulting or involving claim of that process.